

## Dunlop Hiflex Life Raft Hose 281E

SPECIFICATION : 281E

Nominal Bore Size		Mean Diameter Over Wire		Max Diameter Over Cover		Maximum Working Pressure		Minimum Burst Pressure		Minimum Bend Radius		Approx Weight	
Inch	MM	Inch	MM	Inch	MM	PSI	Bar	PSI	Bar	Inch	MM	Lbs/ft	Kg/M
3/8	9.5	0.594	15.1	0.701	17.8	3,620	250	18,100	1,250	2.5	65	0.29	0.43

Product Information

- Description : Low temperature 2 wire braid life raft hose
- Liner : Black; oil resistant ultra low temperature synthetic rubber
- Cover : Black; oil, water, ozone, flame & ultra low temperature resistant synthetic rubber
- Reinforcement : Two braids of high tensile steel wire
- Temperature Range : -55°C to +65°C (-67°F to 149°F)

Applications

Life raft inflation systems - particularly suitable where low temperature flexibility is of paramount importance.

These products may be used with gaseous Carbon Dioxide, Nitrogen and mixtures of the two.

Issue	1					Drawn	Approved	Date
D&ECN	DH4 368					<b>DCR</b>	<b>PG</b>	<b>22.12.03</b>
Date	17.0.03					<b>MS.51281E A</b>		

