

Dunlop Hiflex SP22

Specification for : 2SPL

Nominal Bore Size		Mean Diameter OverWire		Mean Diameter OverCover		Maximum Working Pressure		Minimum Burst Pressure		Minimum Bend Radius		Approx Weight	
Inch	MM	Inch	MM	Inch	MM	PSI	Bar	PSI	Bar	Inch	MM	Lbs/ft	Kg/M
3/8	9.5	0.657	16.7	0.839	21.3	5,000	345	20,000	1380	5.0	130	0.41	0.61
1/2	12.7	0.780	19.8	0.965	24.5	5,000	345	20,000	1380	6.0	150	0.58	0.87
5/8	15.9	0.906	23.0	1.091	27.7	4,250	295	17,000	1180	7.5	190	0.68	1.01
3/4	19.0	1.063	27.0	1.248	31.7	3,750	258	15,000	1032	9.0	230	0.83	1.23
1	25.4	1.374	34.9	1.547	39.3	3,000	207	12,000	828	12.0	300	1.12	1.66
1.1/4	31.8	1.748	44.4	1.969	50.0	2,250	155	9,000	620	15.0	380	1.76	2.62

Product Information

Description : Heavy duty high pressure 2 wire braid hydraulic hose
 Liner : Black; oil resistant synthetic rubber
 Cover : Black; oil, water, ozone & flame resistant synthetic rubber
 Reinforcement : Two braids of high tensile steel wire
 Temperature Range : -40°C to +100°C (-40°F TO +212°F); intermittent use up to +125°C (257°F)*

* Petroleum based fluids only. Water based fluids at temperatures -40°C to +70°C (-40°F to +158°F)

Applications

Hydraulic systems with petroleum or water/glycol based fluids and for field and lubricating oils

Issue	1						Drawn	Approved	Date
D&ECN	DH 4368						DCR	PG	22.12.03
Date	17.09.03						MS.512SPL.A		