

Dunlop Hiflex Low Temperature 2SN

SPECIFICATION : 224E

Nominal Bore Size		Mean Diameter Over Wire		Maximum Diameter Over Cover		Maximum Working Pressure		Minimum Burst Pressure		Minimum Bend Radius		Approx Weight	
Inch	MM	Inch	MM	Inch	MM	PSI	Bar	PSI	Bar	Inch	MM	Lbs/ft	Kg/M
1/4	6.3	0.500	12.7	0.618	15.7	5,800	400	23,200	1600	4.0	100	0.25	0.37
5/16	8.0	0.563	14.3	0.681	17.3	5,075	350	20,300	1400	4.5	115	0.28	0.42
3/8	9.5	0.657	16.7	0.776	19.7	4,785	330	19,140	1320	5.0	130	0.36	0.53
1/2	12.7	0.780	19.8	0.906	23.0	3,985	275	15,950	1100	7.0	180	0.42	0.63
5/8	15.9	0.906	23.0	1.035	26.3	3,625	250	14,500	1000	8.0	200	0.51	0.76
3/4	19.0	1.063	27.0	1.189	30.2	3,115	215	12,325	850	9.5	240	0.63	0.94
1	25.4	1.374	34.9	1.528	38.8	2,390	165	9,425	650	12.0	300	0.96	1.43
1.1/4	31.8	1.748	44.4	1.921	48.8	1,810	125	7,250	500	16.5	420	1.60	2.38

Product Information

- Description** : Medium pressure 2 wire braid low temperature hydraulic hose
- Liner** : Black; oil resistant ultra low temperature synthetic rubber
- Cover** : Black; oil, water, ozone, flame & ultra low temperature resistant synthetic rubber
- Reinforcement** : Two braids of high tensile steel wire
- Temperature Range** : -55°C to +100°C (-67°F TO +212°F); intermittent use up to +125°C (257°F)*

* Petroleum based fluids only. Water based fluids at temperatures -55°C to +70°C (-67°F to +158°F)

Applications

Hydraulic systems with petroleum or water/glycol based fluids and for field and lubricating oils

Issue	1					Drawn	Approved	Date
D&ECN	DH 4368					DCR	PG	22.12.03
Date	17.09.03					MS.51224E.A		